

Enterprise Mobile Computer

BIP-5000 Black



pibion
Empowering Mobility

BIP-5000Black

INDUSTRIES



Retail



Public Transport



Hospitality



Healthcare



Finance

KEY FEATURES & BENEFITS

Functionality



Barcode Scanner, A-GPS, HSDPA, WLAN

BIP-5000Black is the AutoID PDA integrated with 1D/2D Barcode Scanner, A-GPS as well as Voice and Data Communication and WLAN. The ability to collect barcode data and transfer data with high-speed in a single device improves field force automation and increases productivity.

Rugged



IP65, 1.5m Drop, -20°C to 55°C

BIP-5000Black is built to withstand harsh work environments.

- Rated IP65 for protection against rain and dust
- Withstand multiple 1.5m drops to steel surface
- Operate in a temperature range of -20°C to 55°C

Compatibility



Windows Mobile or Windows CE

BIP-5000Black with Windows Mobile-based operating system makes it easy to install custom applications and access to your work PC. The device allows you to manage real-time information all about work documents, customers, inventory, delivery and much more without any restraints of time or place.

Ergonomic



3.5" Touch Screen, Numeric Keypad

- 3.5" display delivers excellent graphic capability and readability.
- Touch screen and numeric keypad provide simple and easy operation.
- Sleek, compact and hand-held device grants you easy control of your work with one hand on the go.


Enterprise Mobile Computer



APPLICATIONS



 **1D Barcode & PDF417**
Laser Class II


 **2D Barcode**
CMOS Imager

 **GPS**
Integrated A-GPS

 **Camera**
2 megapixel

 **CPU**
PXA320, 806MHz

 **Memory**
128MB RAM 256MB ROM

 **Battery**
3.7V, 2,300mAh, Li-ion
3.7V, 3,700mAh, Li-ion

 **Bluetooth**
Bluetooth Class II V2.0+EDR



BIP-5000Black

SPECIFICATIONS

PHYSICAL CHARACTERISTICS	
DIMENSIONS (W x H x D)	75 x 150.3 x 24.9mm / 3.0 x 5.9 x 1.0 inch
WEIGHT	Excluding battery: 253g / Including standard battery: 314g / Including extened battery: 347g
DISPLAY	3.5" QVGA with backlight, TFT-LCD, 260K, 240 x 320
TOUCH PANEL	Analog resistance type
KEYPAD	Numeric keypad
STANDARD BATTERY	Rechargeable, 3.7V, 2,300mAh, Li-ion
EXTENDED BATTERY (optional)	Rechargeable, 3.7V, 3,700mAh, Li-ion
EXPANSION SLOT	Customer-accessible MiniSD slot for removable memory card up to 2G
SIM SLOT	1 SIM
AUDIO	Speaker, Headset jack
CAMERA	2 megapixel color camera with LED flash / Ultra bright LED flash (optional)
GPS	Integrated A-GPS
PERFORMANCE CHARACTERISTICS	
CPU	PXA 320, 806MHz
OS	Windows Mobile 6.1
MEMORY	128MB RAM / 256MB ROM
INTERFACE	RS-232C, USB 1.1 Host & Client, Ethernet via cradle
USER ENVIRONMENT CHARACTERISTICS	
OPERATING TEMP	-20°C to 55°C / -4°F to 131°F
STORAGE TEMP	-25°C to 70°C / -13°F to 158°F
HUMIDITY	93% non-condensing
DROP SPEC	5ft./1.5m drop to steel surface, 2drops per 6 sides
RAIN/DUST PROTECTION	IP65
INTEGRATED RADIO	
WWAN RADIO	GSM / GPRS / eGPRS (850, 900, 1800, 1900 MHz)
WLAN RADIO	IEEE 802.11b/g
WPAN RADIO	Bluetooth Class II V2.0+EDR, IrDA 1.2
DATA CAPTURE	
BARCODE SCANNER	1D&PDF417 Laser Class II or 1D&2D CMOS Imager



ACCESSORIES



Cradle

Battery

Protection Film

Adapter

Adapter Connector

USB Cable

Stylus Pen

Tether

Bluebird

1242, Gaepo-dong, Gangnam-gu, Seoul, Korea (ROK)

T. +82. 70.7730.8000 F. +82. 2.548.0870

www.mypidion.com www.bluebird.co.kr cn.bluebirdsoft.com

Copyright © 2009 Bluebird Soft Inc. All rights reserved.

Bluebird and Pidion are registered trademarks and symbols of Bluebird Soft Inc.

Features and specifications are subject to change without prior notice.

Update: December 2009